

## Safety Data Sheet

acc. to OSHA HCS

Printing date 01/18/2024

Revision date 01/18/2024

Page 1/10

### **1 Identification**

- Product identifier
- Trade name: <u>5(S)-HETE MaxSpec® Standard</u>
- · Synonym 5(S)-Hydroxyeicosatetraenoic Acid; 5S-hydroxy-6E,8Z,11Z,14Z-eicosatetraenoic acid
- · Article number: 10007243
- **Application of the substance / the mixture** This product is for research use - Not for human or veterinary diagnostic or therapeutic use.
- Details of the supplier of the safety data sheet
   Manufacturer/Supplier: Cayman Chemical Co.
   1180 E. Ellsworth Rd. Ann Arbor, MI 48108
- USA • Information department: Product safety department • Emergency telephone number: During normal opening times: +1 (734) 971-3335 US/CANADA: 800-424-9300 Outside US/CANADA: 703-741-5970

## 2 Hazard(s) identification

#### · Classification of the substance or mixture

GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



H319 Causes serious eye irritation.

Eye Irritation 2A

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



· Signal word Danger

(Contd. on page 2)

Printing date 01/18/2024

Revision date 01/18/2024

## Trade name: 5(S)-HETE MaxSpec® Standard

	(Contd. from page 1)			
• Hazard stateme				
	nmable liquid and vapor.			
	H319 Causes serious eye irritation.			
· Precautionary s				
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.			
P233	Keep container tightly closed.			
P240	Ground/bond container and receiving equipment.			
P241	Use explosion-proof electrical/ventilating/lighting/equipment.			
P242	Use only non-sparking tools.			
P243	Take precautionary measures against static discharge.			
P264	Wash thoroughly after handling.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P303+P361+P3	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with			
	water/shower.			
P305+P351+P3	38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if			
D007 . D040	present and easy to do. Continue rinsing.			
P337+P313	If eye irritation persists: Get medical advice/attention.			
P370+P378	In case of fire: Use CO2, powder or water spray to extinguish.			
P403+P235	Store in a well-ventilated place. Keep cool.			
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.			
· Classification system:				
NFPA ratings (s				
INFFA faulitys (s	Scale 0 - 4)			
He	alth = 2			
Fire	e = 3			
2 0 Reactivity = 0				
<ul><li>▼</li><li>✓</li></ul>				
· HMIS-ratings (s	scale 0 - 4)			
HEALTH 2 He	ealth - 2			
HEALTH     2       FIRE     3       Fire     3				
	eactivity = 0			
Other hazards				
· Results of PBT and vPvB assessment				
• <b>PBT:</b> Not applicable.				
• vPvB: Not applicable.				
3 Composition/information on ingredients				
3 Composition	information on ingredients			

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous compon	ents:	
CAS: 64-17-5 RTECS: KQ6300000		99.999%
· Other ingredients		
CAS: 70608-72-9 RTECS: JX3873000	5(S)-HETE	0.001%
		US

(Contd. on page 3)

Printing date 01/18/2024

Revision date 01/18/2024

#### Trade name: 5(S)-HETE MaxSpec® Standard

(Contd. from page 2)

#### **4 First-aid measures**

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### **5 Fire-fighting measures**

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
  Wear protective equipment. Keep unprotected persons away.
   Environmental precautions:
  Dilute with plenty of water.
  Do not allow to enter sewers/ surface or ground water.
   Methods and material for containment and cleaning up:
  Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. • **Reference to other sections**
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:	
64-17-5 ethanol	1,800 ppm
· PAC-2:	
64-17-5 ethanol	3300* ppm
· PAC-3:	
64-17-5 ethanol	15000* ppm
· · ·	

(Contd. on page 4)

Printing date 01/18/2024

Revision date 01/18/2024

#### Trade name: 5(S)-HETE MaxSpec® Standard

(Contd. from page 3)

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling
- No special precautions are necessary if used correctly. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Avoid prolonged or repeated exposure.
- Keep away from sources of ignition.
- Take precautionary measures against static discharge.re.
- Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage: Store in accordance with information listed on the product insert.
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

Control parameters

· Components with limit values that require monitoring at the workplace:

#### 64-17-5 ethanol

PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

- REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm
- TLV Short-term value: 1000 ppm A3

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Printing date 01/18/2024

Revision date 01/18/2024

#### Trade name: 5(S)-HETE MaxSpec® Standard

(Contd. from page 4) Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## • **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

### **9** Physical and chemical properties

· Information on basic physical and c	chemical properties
<ul> <li>General Information</li> <li>Appearance: <ul> <li>Form:</li> <li>Color:</li> </ul> </li> <li>Odor:</li> <li>Structural Formula</li> <li>Molecular Weight</li> <li>Odor threshold:</li> <li>Formulation</li> </ul>	Liquid According to product specification Alcohol-like C20H32O3 320.5 g/mol Not determined. A solution in ethanol at 10 µg/ml
· pH-value:	Not determined.
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>	-114 °C (-173.2 °F) 78 °C (172.4 °F)
· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
· Explosion limits: Lower: Upper:	3.3 Vol % 19 Vol %
<ul> <li>Vapor pressure at 20 °C (68 °F):</li> <li>Vapor pressure at 50 °C (122 °F):</li> </ul>	59 hPa (44.3 mm Hg) 280 hPa (210 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> </ul>	0.79 g/cm³ (6.59255 lbs/gal) Not determined.
	(Contd. on page 6)

US

Printing date 01/18/2024

#### Revision date 01/18/2024

#### Trade name: 5(S)-HETE MaxSpec® Standard

		(Contd. from page 5)	
<ul> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	Not determined. Not determined.		
<ul> <li>Solubility in / Miscibility with Water at 20 °C (68 °F):</li> </ul>	1,000 g/l		
· Partition coefficient (n-octanol/w	· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:			
Dynamic at 20 °C (68 °F):	1.2 mPas		
Kinematic:	Not determined.		
· Solvent content:			
Organic solvents:	100.0 %		
VOC content:	100.00 %		
	1,000.0 g/l / 8.35 lb/gal		
Solids content:	0.0 %		
· Other information	No further relevant information available.		

#### **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: strong oxidizing agents
- · Hazardous decomposition products: carbon dioxide, carbon monoxide

#### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

#### 64-17-5 ethanol

Oral

LD50 10,470 mg/kg (rat)

OECD Test Guideline 401

Inhalative LC50/4 h 117–125 mg/l (rat) OECD 403 (rat)

#### Primary irritant effect:

• on the skin: No irritant effect.

- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 7)

US -

Printing date 01/18/2024

#### Revision date 01/18/2024

#### Trade name: 5(S)-HETE MaxSpec® Standard

(Contd. from page 6)

1

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- 64-17-5 ethanol
- · NTP (National Toxicology Program)

None of the ingredients is listed.

#### OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · **Bioaccumulative potential** No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN1170
· UN proper shipping name	
DOT	Ethanol solutions
·IMDG	ETHANOL SOLUTION (ETHYL ALCOH)
	SOLUTION)
·IATA	Ethanol solution

Printing date 01/18/2024

Revision date 01/18/2024

(Contd. from page 7)

## Trade name: 5(S)-HETE MaxSpec® Standard

· Transport hazard class(es)	
DOT	
FLAMARE DOUD	
· Class · Label	3 Flammable liquids 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids 3
<ul> <li>Packing group</li> <li>DOT, IMDG, IATA</li> </ul>	П
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
<ul> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> </ul>	F-E,S-D
· Stowage Category	A
<ul> <li>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IATA · Remarks:	When sold in quantities of less than or equal to 1 mL, or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.
· UN "Model Regulation":	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II
	US

(Contd. on page 9)

Revision date 01/18/2024

#### Trade name: 5(S)-HETE MaxSpec® Standard

Printing date 01/18/2024

(Contd. from page 8)

	ealth and environmental regulations/legislation specific for the substance or mixtur relevant information available.	e
· Section 3	55 (extremely hazardous substances):	
None of t	ne ingredients is listed.	
· Section 3	13 (Specific toxic chemical listings):	
None of t	ne ingredients is listed.	
· TSCA (To	exic Substances Control Act):	
64-17-5	ACT ACT	١V
· Hazardou	us Air Pollutants	
None of t	ne ingredients is listed.	
· Propositi		
	Is known to cause cancer:	
None of t	ne ingredients is listed.	
	Is known to cause reproductive toxicity for females:	
None of t	ne ingredients is listed.	
	Is known to cause reproductive toxicity for males:	
None of t	ne ingredients is listed.	
· Chemica	Is known to cause developmental toxicity:	
64-17-5	sthanol	
· Carcinog	enic categories	
· EPA (Env	vironmental Protection Agency)	
None of t	ne ingredients is listed.	
· TLV (Thr	eshold Limit Value)	_
64-17-5	ethanol	A
NIOSH-C	a (National Institute for Occupational Safety and Health)	_

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

- · Department issuing SDS: Environment protection department.
- · Contact: -
- Date of preparation / last revision 01/18/2024
- **Abbreviations and acronyms:** IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

Printing date 01/18/2024

Revision date 01/18/2024

### Trade name: 5(S)-HETE MaxSpec® Standard

	(Contd. from page 9)
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flammable Liquids 2: Flammable liquids – Category 2	
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A	
* * Data compared to the previous version altered.	
	115