



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

1 Identification

- **Product identifier**
- **Trade name:** 14,15-Leukotriene A4 methyl ester
- **Article number:** 10011359
- **Application of the substance / the mixture**
This product is for research use - Not for human or veterinary diagnostic or therapeutic use.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Cayman Chemical Co.
1180 E. Ellsworth Rd.
Ann Arbor, MI 48108
USA
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (734) 971-3335
US/CANADA: 800-424-9300
Outside US/CANADA: 703-741-5970

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS09 Environment

Aquatic Chronic 2

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 1)



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

GHS09

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Hexane

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 2)

P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use CO ₂ , powder or water spray to extinguish.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 110-54-3 RTECS: MN9275000	Hexane	98.99%
CAS: 121-44-8 RTECS: YE0175000	Triethylamine	1.0%

- **Other ingredients**

75290-58-3	14,15-Leukotriene A4 methyl ester	0.01%
------------	-----------------------------------	-------

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
67-56-1 During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

110-54-3	Hexane	260 ppm
121-44-8	Triethylamine	1 ppm

· **PAC-2:**

110-54-3	Hexane	2900* ppm
121-44-8	Triethylamine	170 ppm

· **PAC-3:**

110-54-3	Hexane	8600** ppm
121-44-8	Triethylamine	1,000 ppm

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** Store in accordance with information listed on the product insert.
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

110-54-3 Hexane

PEL	Long-term value: 1800 mg/m ³ , 500 ppm
REL	Long-term value: 180 mg/m ³ , 50 ppm
TLV	Long-term value: 50 ppm Skin; BEI

121-44-8 Triethylamine

PEL	Long-term value: 100 mg/m ³ , 25 ppm
TLV	Short-term value: 1 ppm Long-term value: 0.5 ppm Skin, A4

- **Ingredients with biological limit values:**

110-54-3 Hexane

BEI	0.5 mg/L Medium: urine Time: end of shift Parameter: 2.5-Hexanedione without hydrolysis
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 5)

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Fluid
· Color:	Colorless
· Odor:	Characteristic
· Structural Formula	C ₂₁ H ₃₂ O ₃
· Molecular Weight	332.5 g/mol
· Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

· Melting point/Melting range:	-95 °C (-139 °F)
· Boiling point/Boiling range:	69 °C (156.2 °F)

- **Flash point:** -26 °C (-14.8 °F)

- **Flammability (solid, gaseous):** Highly flammable.

- **Auto igniting:** 240 °C (464 °F)

- **Decomposition temperature:** Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 6)

· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.4 Vol %
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
· Vapor pressure at 50 °C (122 °F):	540 hPa (405 mm Hg)
· Density at 20 °C (68 °F):	0.66 g/cm ³ (5.5077 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water at 20 °C (68 °F):	0.1 g/l
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.0 %
VOC content:	99.99 %
	999.9 g/l / 8.34 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	46,000 mg/kg (rat)
Dermal	LD50	110,000 mg/kg
Inhalative	LC50/4 h	1,100 mg/l

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 7)

110-54-3 Hexane

Oral	LD50	15,840 mg/kg (rat)
Inhalative	LC50/4 h	48,000 mg/m ³ (rat)
	TCLO	5,400 mg/m ³ /10m (hmn)
Irritation of eyes	Irritation	10 mg (rabbit) mild
	Interperitoneal LDLO Data	9,100 mg/kg (rat) 10 mg (rabbit) mild

121-44-8 Triethylamine

Oral	LD50	460 mg/kg (rat)
Dermal	LD50	570 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxic effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester




· **Other adverse effects** No further relevant information available.

(Contd. from page 8)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | UN1993 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG · IATA | Flammable liquids, n.o.s. (Hexanes)
FLAMMABLE LIQUID, N.O.S. (HEXANES), MARINE POLLUTANT
Flammable liquid, n.o.s. (HEXANES) |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · IMDG | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | II |

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 9)

· Environmental hazards:	Product contains environmentally hazardous substances: Hexane
· Marine pollutant:	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IATA	
· Remarks:	When sold in quantities of less than or equal to 1 mL, or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (HEXANES), 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

110-54-3 Hexane

121-44-8 Triethylamine

- **TSCA (Toxic Substances Control Act):**

110-54-3 Hexane

ACTIVE

121-44-8 Triethylamine

ACTIVE

- **Hazardous Air Pollutants**

110-54-3 Hexane

121-44-8 Triethylamine

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 10)

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

110-54-3 Hexane

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

110-54-3 Hexane

II

- **TLV (Threshold Limit Value)**

121-44-8 Triethylamine

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

- **Department issuing SDS:** Environment protection department.

- **Contact:** -

- **Date of preparation / last revision** 06/02/2023

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

(Contd. on page 12)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2023

Revision date 06/02/2023

Trade name: 14,15-Leukotriene A4 methyl ester

(Contd. from page 11)

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

US