

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Revision date 05/06/2024

Page 1/11

1 Identification

- Product identifier
- Trade name: <u>5-methoxy DiPT (exempt preparation)</u>
- · Synonym 5-methoxy-N,N-bis(1-methylethyl)-1H-indole-3-ethanamine
- · Article number: 15697
- **Application of the substance / the mixture** This product is for research use - Not for human or veterinary diagnostic or therapeutic use.
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Cayman Chemical Co.
 1180 E. Ellsworth Rd. Ann Arbor, MI 48108
- USA • Information department: Product safety department • Emergency telephone number: During normal opening times: +1 (734) 971-3335 US/CANADA: 800-424-9300 Outside US/CANADA: 703-741-5970

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flammable Liquids 2

GHS06 Skull and crossbones

Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3 H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to the central nervous system and the visual organs.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

⁻ US

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

| Hererd nietes | (Contd. from page 1 |
|-----------------------------|---|
| Hazard pictog | rams |
| | |
| < {} > | |
| | |
| GHS02 GHS | 506 GHS08 |
| Signal word D |)anger |
| • Hazard-detern Methanol | nining components of labeling: |
| Hazard statem | nents |
| H225 | Highly flammable liquid and vapor. |
| H301+H311+H | 1331 Toxic if swallowed, in contact with skin or if inhaled. |
| H370 | Causes damage to the central nervous system and the visual organs. |
| Precautionary | v statements |
| P210 | Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray. |
| P264 | Wash thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301+P310 | If swallowed: Immediately call a poison center/doctor. |
| P321 | Specific treatment (see on this label). |
| P330 | Rinse mouth. |
| P303+P361+P | 353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin wit |
| 0201-0210 | water/shower. |
| P304+P340 P307+P311 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed: Call a POISON CENTER or doctor/physician. |
| P312 | Call a poison center/doctor if you feel unwell. |
| P361+P364 | Take off immediately all contaminated clothing and wash it before reuse. |
| P370+P378 | In case of fire: Use CO2, powder or water spray to extinguish. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international |
| | regulations. |
| Classification | 6 |
| NFPA ratings | |
| | |
| | lealth = 2 |
| | ire = 3 |
| V R | teactivity = 0 |
| | |

· HMIS-ratings (scale 0 - 4)

| HEALTH *2 | Health = *2 |
|--------------|----------------|
| | Fire = 3 |
| REACTIVITY 0 | Reactivity = 0 |

(Contd. on page 3)

US

Printing date 05/06/2024

Revision date 05/06/2024

(Contd. from page 2)

99.9%

0.1%

Trade name: 5-methoxy DiPT (exempt preparation)

- · Other hazards
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

| CAS: 67-56-1 | Methanol |
|------------------|----------|
| RTECS: PC1400000 | |

Other ingredients

CAS: 4021-34-5 5-methoxy DiPT RTECS: NL8504865

4 First-aid measures

Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Special hazards arising from the substance or mixture
- 67-56-1During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

(Contd. on page 4)

US ·

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

| | (Contd. from page 3) |
|--|----------------------|
| Wear protective equipment. Keep unprotected persons away. | |
| Environmental precautions: | |
| Dilute with plenty of water. | |
| Do not allow to enter sewers/ surface or ground water. | |
| • Methods and material for containment and cleaning up: | |
| Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sav | vdust). |
| Dispose contaminated material as waste according to section 13. | |
| Ensure adequate ventilation. | |
| Reference to other sections | |
| See Section 7 for information on safe handling. | |
| See Section 8 for information on personal protection equipment. | |
| See Section 13 for disposal information. | |
| Protective Action Criteria for Chemicals | |
| · PAC-1: | |
| 67-56-1 Methanol | 530 ppm |
| · PAC-2: | |
| 67-56-1 Methanol | 2,100 ppm |
| · PAC-3: | |
| 67-56-1 Methanol | 7200* ppm |
| | |

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information account explanation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage: Store in accordance with information listed on the product insert.
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

67-56-1 Methanol

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm

Long-term value: 260 mg/m³, 200 ppm Skin

(Contd. on page 5)

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

(Contd. from page 4) TLV Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEIc · Ingredients with biological limit values: 67-56-1 Methanol BEI 15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of guality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection:



Tightly sealed goggles

(Contd. on page 6)

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

(Contd. from page 5)

| Information on basic physical and chemical properties General Information Appearance: Form: Liquid Color: According to product specification Odor: Accohol-like Structural Formula C17H26N2O Molecular Weight 274.4 g/mol Otor threshold: Not determined. Formulation A solution in methanol PH-value: Not determined. Change in condition Melting point/Beiling range: -98 °C (-144.4 °F) Boiling point/Beiling range: 64.7 °C (148.5 °F) Flash point: 11 °C (51.8 °F) Flammability (solid, gaseous): Highly flammable. Auto igniting: 455 °C (851 °F) Decomposition temperature: Not determined. Ignition temperature: Product is not selfigniting. Danger of explosion: Product is not selfigniting. Lower: 5.5 Vol % Upper: 44 Vol % Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) Density at 20 °C (68 °F): 1000 g/l Partition coefficient (n-octanol/water): Not determined. Vapor density Not determined. Vapor and ces (68 °F): 1000 g/l Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Viscosity: Dynamic: Not determined. Viscosity: Dynamic: Not determined. Solubility in / Miscibility with Water at 20 °C (68 °F): 1000 g/l Partition coefficient (n-octanol/water): Not determined. Viscosi | 9 Physical and chemical prope | |
|--|--|--|
| Form: Liquid Color: According to product specification Odor: Alcohol-like Structural Formula C17H26N2O Molecular Weight 274.4 g/mol Odor threshold: Not determined. Formulation A solution in methanol * pH-value: Not determined. * Change in condition Metting point/Boiling range: -98 °C (-144.4 °F) Boiling point/Boiling range: Boiling point/Boiling range: -98 °C (-148.5 °F) * Flash point: 11 °C (51.8 °F) * Flammability (solid, gaseous): Highly flammable. • Auto igniting: 455 °C (851 °F) • Decomposition temperature: Not determined. • Ignition temperature: Product is not selfigniting. • Danger of explosion: Product is not selfigniting. • Danger of explosion: Product is not selfigniting. • Upper: 44 Vol % • Vapor pressure at 20 °C (68 °F): 0.79 g/cm² (6.59255 lbs/gal) • Relative density Not determined. • Vapor density Not determined. • Vapor density Not determined. • Vapor density< | General Information | chemical properties |
| FormulationA solution in methanolpH-value:Not determined.Change in condition Melting point/Melting range: Boiling point/Boiling range: 64.7 °C (144.4 °F) Boiling point/Boiling range: 64.7 °C (148.5 °F)Flash point:11 °C (51.8 °F)Flamability (solid, gaseous):Highly flammable.Auto igniting:455 °C (851 °F)Decomposition temperature:Not determined.Ignition temperature:Product is not selfigniting.Danger of explosion:Product is not selfigniting.Changer of explosion:5.5 Vol % 4 Vol %Upper:44 Vol %Vapor pressure at 20 °C (68 °F):128 hPa (96 mm Hg)Density at 20 °C (68 °F):0.79 g/cm³ (6.59255 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Vapor densityNot determined.Vapor coefficient (n-octanol/water): Not determined.Viscosity:Not determined.Viscosity:Not determined.Viscosity:Not determined.Viscosity:Not determined.Viscosity:Not determined.Viscosity:Not determined.Solvent content:99.90 % 99.90 % 99.90 %VOC content:99.90 % 99.90 g/l / 8.34 lb/gal | Form: Color: · Odor: · Structural Formula · Molecular Weight | According to product specification Alcohol-like C17H26N2O 274.4 g/mol |
| Change in condition Melting point/Melting range: -98 °C (-144.4 °F) Boiling point/Boiling range: 64.7 °C (148.5 °F) Flash point: 11 °C (51.8 °F) Flammability (solid, gaseous): Highly flammable. Auto igniting: 455 °C (851 °F) Decomposition temperature: Not determined. Ignition temperature: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive air vapor mixtures are possible. Explosion limits: 5.5 Vol % Lower: 5.5 Vol % Upper: 44 Vol % Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal) Relative density Not determined. Vapor density Not determined. Vapor density Not determined. Solubility in / Miscibility with Water at 20 °C (68 °F): 1000 g/l Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Viscosity: Dynamic: Not determined. Viscosity: Dynamic: Not determined. Solvent content: O | | |
| Melting point/Melting range: -98 °C (-144.4 °F) Boiling point/Boiling range: 64.7 °C (148.5 °F) * Flash point: 11 °C (51.8 °F) * Flammability (solid, gaseous): Highly flammable. • Auto igniting: 455 °C (851 °F) • Decomposition temperature: Not determined. • Ignition temperature: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive ail vapor mixtures are possible. • Explosion limits: 5.5 Vol % Lower: 5.5 Vol % Upper: 44 Vol % • Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) • Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal) Relative density Not determined. • Vapor density Not determined. • Vapor density Not determined. • Vater at 20 °C (68 °F): 1000 g/l • Partition coefficient (n-octanol/water): Not determined. • Viscosity: Dynamic: Dynamic: Not determined. • Viscosity: 99.9 % Over content: 99.9 % • Over content: 99.9 % • VO | · pH-value: | Not determined. |
| Flammability (solid, gaseous): Highly flammable. Auto igniting: 455 °C (851 °F) Decomposition temperature: Not determined. Ignition temperature: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive air vapor mixtures are possible. Explosion limits: Lower: 5.5 Vol % Lower: 5.5 Vol % Upper: 44 Vol % Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal) Relative density Not determined. Vapor density Not determined. Vapor density Not determined. Solubility in / Miscibility with Water at 20 °C (68 °F): Viscosity: Dynamic: Dynamic: Not determined. Viscosity: Dynamic: Dynamic: Not determined. Solvent content: 99.9 % Organic solvents: 99.9 % 99.90 g/l / 8.34 lb/gal 999.0 g/l / 8.34 lb/gal | Melting point/Melting range: | |
| Auto igniting: 455 °C (851 °F) Decomposition temperature: Not determined. Ignition temperature: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive air vapor mixtures are possible. Explosion limits: Lower: Lower: 5.5 Vol % Upper: 44 Vol % Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal)) Relative density Not determined. Vapor density Not determined. Vapor density Not determined. Solubility in / Miscibility with Water at 20 °C (68 °F): Viscosity: Dynamic: Dynamic: Not determined. Viscosity: Dynamic: Dynamic: Not determined. Solvent content: 99.9 % Organic solvents: 99.9 % VOC content: 99.90 % 999.0 g/l / 8.34 lb/gal 999.0 g/l / 8.34 lb/gal | · Flash point: | 11 °C (51.8 °F) |
| Decomposition temperature: Not determined. Ignition temperature: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive air vapor mixtures are possible. Explosion limits: Lower: 5.5 Vol % Upper: 44 Vol % Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal) Relative density Not determined. Vapor density Not determined. Exploration rate Not determined. Solubility in / Miscibility with Wot determined. Viscosity: Dynamic: Dynamic: Not determined. Viscosity: Dynamic: Dynamic: Not determined. Solvent content: 09.9 % Organic solvents: 99.9 % 99.0 g/l / 8.34 lb/gal 99.0 g/l / 8.34 lb/gal | · Flammability (solid, gaseous): | Highly flammable. |
| Ignition temperature: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive air vapor mixtures are possible. Explosion limits: | · Auto igniting: | 455 °C (851 °F) |
| Danger of explosion: Product is not explosive. However, formation of explosive air vapor mixtures are possible. Explosion limits: 5.5 Vol % Lower: 5.5 Vol % Upper: 44 Vol % Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal) Relative density Not determined. Vapor density Not determined. Vapor density Not determined. Vapor density Not determined. Vater at 20 °C (68 °F): 1000 g/l Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: 09.9 % Organic solvents: 99.9 % 99.0 g/l / 8.34 lb/gal 99.0 g/l / 8.34 lb/gal | · Decomposition temperature: | Not determined. |
| • Explosion limits: 5.5 Vol % Lower: 5.5 Vol % Upper: 44 Vol % • Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) • Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal) • Relative density Not determined. • Vapor density Not determined. • Vapor density Not determined. • Vapor advanta Not determined. • Vapor density Not determined. • Vapor advanta Not determined. • Vapor advanta Not determined. • Viscosity in / Miscibility with Water at 20 °C (68 °F): • Viscosity: Dynamic: Dynamic: Not determined. • Viscosity: Not determined. Organic solvents: 99.9 % • VOC content: 99.90 % • 99.90 % 999.0 g/l / 8.34 lb/gal | · Ignition temperature: | Product is not selfigniting. |
| Lower:5.5 Vol % Upper:Upper:44 Vol %Vapor pressure at 20 °C (68 °F):128 hPa (96 mm Hg)• Density at 20 °C (68 °F):0.79 g/cm³ (6.59255 lbs/gal)• Relative densityNot determined.• Vapor densityNot determined.• Vapor densityNot determined.• Vapor densityNot determined.• Solubility in / Miscibility with Water at 20 °C (68 °F):1000 g/l• Partition coefficient (n-octanol/water):Not determined.• Viscosity: Dynamic: Kinematic:Not determined.• Viscosity: Organic solvents:99.9 % 99.9 % 99.0 g/l / 8.34 lb/gal | · Danger of explosion: | Product is not explosive. However, formation of explosive air vapor mixtures are possible. |
| • Density at 20 °C (68 °F): 0.79 g/cm³ (6.59255 lbs/gal) • Relative density Not determined. • Vapor density Not determined. • Vapor density Not determined. • Evaporation rate Not determined. • Solubility in / Miscibility with Water at 20 °C (68 °F): • Vater at 20 °C (68 °F): 1000 g/l • Partition coefficient (n-octanol/water): Not determined. • Viscosity: Dynamic: Dynamic: Not determined. • Kinematic: Not determined. • Voc content: 99.9 % • VOC content: 99.90 % • 999.0 g/l / 8.34 lb/gal | Lower: | |
| Relative density Not determined. Vapor density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water at 20 °C (68 °F): 1000 g/l Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Dynamic: Not determined. Kinematic: Not determined. Solvent content: 99.9 % Organic solvents: 99.90 % 999.0 g/l / 8.34 lb/gal | · Vapor pressure at 20 °C (68 °F): | 128 hPa (96 mm Hg) |
| Water at 20 °C (68 °F): 1000 g/l • Partition coefficient (n-octanol/water): Not determined. • Viscosity: Not determined. Dynamic: Not determined. Kinematic: Not determined. • Solvent content: 99.9 % • VOC content: 99.90 % • 999.0 g/l / 8.34 lb/gal | Relative density Vapor density | Not determined. Not determined. |
| · Viscosity: Dynamic: Not determined. Dynamic: Not determined. Kinematic: Not determined. · Solvent content: 99.9 % VOC content: 99.90 % 999.0 g/l / 8.34 lb/gal | | 1000 g/l |
| Dynamic: Not determined. Kinematic: Not determined. Solvent content: 99.9 % Organic solvents: 99.90 % VOC content: 999.0 g/l / 8.34 lb/gal | · Partition coefficient (n-octanol/wat | er): Not determined. |
| Organic solvents: 99.9 % VOC content: 99.90 % 999.0 g/l / 8.34 lb/gal | Dynamic: | |
| Solids content: 0.1 % | Organic solvents: | 99.90 % |
| | Solids content: | 0.1 % |

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

(Contd. from page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· **Incompatible materials:** oxidizing agents, reducing agents

· Hazardous decomposition products: carbon dioxide, carbon monoxide

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

| ATE (Acute Toxicity Estimate) | | | |
|-------------------------------|----------|---|--|
| Oral | LD50 | 100 mg/kg (rat) | |
| Dermal | LD50 | 300 mg/kg (rabbit) | |
| Inhalative | LC50/4 h | 100 mg/kg (rat) 300 mg/kg (rabbit) 3.1 mg/l (rat) | |
| | | | |

67-56-1 Methanol

Г

| Oral | LD50 | 100.1 mg/kg (rat) (Expert judgment) |
|------------|----------|---|
| | | Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table |
| | | 3.1/3.2) Symptoms: Nausea, Vomiting |
| Dermal | LD50 | 300.1 mg/kg (rabbit) (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Tabl 3.1/3.2) |
| Inhalative | LC50/4 h | 3.1 mg/l (rat) (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Tabl 3.1/3.2) |
| | | Symptoms: Irritation symptoms in the respiratory tract. |

• on the skin: No irritant effect.

• on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

(Contd. on page 8)

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

(Contd. from page 7)

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · **Bioaccumulative potential** No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information • UN-Number • DOT, IMDG, IATA • UN proper shipping name • DOT, IATA • IMDG Methanol • IMDG

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

| | (Contd. from page |
|--|---|
| · Transport hazard class(es) | |
| DOT | |
| | |
| | |
| 6 | |
| · Class · Label | 3 Flammable liquids |
| | 3, 6.1 |
| | |
| | |
| Class | 3 Flammable liquids |
| · Label | 3/6.1 |
| ΙΑΤΑ | |
| | |
| Class | 3 Flammable liquids |
| Label | 3 (6.1) |
| · Packing group · DOT, IMDG, IATA | II |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Flammable liquids |
| Hazard identification number (Kemler code): EMS Number: | |
| · EMS Number: · Stowage Category | F-E,S-D B |
| Stowage Code | SW2 Clear of living quarters. |
| Transport in bulk according to Annex II of | |
| MARPOL73/78 and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| DOT | |
| Quantity limitations | On passenger aircraft/rail: 1 L |
| | On cargo aircraft only: 60 L |
| · IMDG · Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) | Code: E2 |
| · · · · · · | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| IATA | |
| · Remarks: | When sold in quantities of less than or equal to 1 m |
| | or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minim |
| | Quantities exemption, per IATA 2.6.10. |
| | (Contd. on page |

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

| | (Contd. from page 9) |
|--------------------------|---|
| | Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity. |
| · UN "Model Regulation": | UN 1230 METHANOL, 3 (6.1), II |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

| Hazardous Air Pollutants 67-56-1 | TIVE |
|---|------|
| Section 313 (Specific toxic chemical listings): 67-56-1 Methanol TSCA (Toxic Substances Control Act): 67-56-1 Methanol AC Hazardous Air Pollutants 67-56-1 Methanol | TIVE |
| 67-56-1 Methanol • TSCA (Toxic Substances Control Act): 67-56-1 67-56-1 Methanol AC • Hazardous Air Pollutants 67-56-1 67-56-1 Methanol AC | TIVE |
| • TSCA (Toxic Substances Control Act): 67-56-1 Methanol • Hazardous Air Pollutants 67-56-1 Methanol | TIVE |
| 67-56-1 Methanol AC Hazardous Air Pollutants 67-56-1 Methanol | TIVE |
| • Hazardous Air Pollutants 67-56-1 | TIVE |
| 67-56-1 Methanol | |
| | |
| | |
| · Proposition 65 | |
| · Chemicals known to cause cancer: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for females: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause developmental toxicity: | |
| 67-56-1 Methanol | |
| · Carcinogenic categories | |
| · EPA (Environmental Protection Agency) | |
| None of the ingredients is listed. | |
| · TLV (Threshold Limit Value) | |
| None of the ingredients is listed. | |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | |
| None of the ingredients is listed. | |

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable. Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

(Contd. on page 11)

US

Printing date 05/06/2024

Revision date 05/06/2024

Trade name: 5-methoxy DiPT (exempt preparation)

| | (Contd. from page 10) |
|--|-----------------------|
| Department issuing SDS: Environment protection department. | |
| Contact: - | |
| Date of preparation / last revision 05/06/2024 / - | |
| • • | |
| Abbreviations and acronyms: | |
| IMDG: International Maritime Code for Dangerous Goods | |
| DOT: US Department of Transportation | |
| IATA: International Air Transport Association | |
| EINECS: European Inventory of Existing Commercial Chemical Substances | |
| ELINCS: European List of Notified Chemical Substances | |
| CAS: Chemical Abstracts Service (division of the American Chemical Society) | |
| NFPA: National Fire Protection Association (USA) | |
| HMIS: Hazardous Materials Identification System (USA) | |
| VOC: Volatile Organic Compounds (USA, EU) | |
| LC50: Lethal concentration, 50 percent | |
| LD50: Lethal dose, 50 percent | |
| PBT: Persistent, Bioaccumulative and Toxic | |
| vPvB: very Persistent and very Bioaccumulative | |
| NIOSH: National Institute for Occupational Safety | |
| OSHA: Occupational Safety & Health TLV: Threshold Limit Value | |
| | |
| PEL: Permissible Exposure Limit | |
| REL: Recommended Exposure Limit | |
| BEI: Biological Exposure Limit | |
| Flammable Liquids 2: Flammable liquids – Category 2 | |
| Acute Toxicity - Oral 3: Acute toxicity – Category 3 Specific Tarret Oran Toxicity – Single Expecting 1: Specific target organ toxicity (single expecting) – Cate | agony 1 |
| Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) - Cate | syory i |
| * Data compared to the previous version altered. | |
| | (|