

Printing date 06/07/2023


Revision date 06/07/2023

Page 1/10

1 Identification

- Product identifier
- · Trade name: (±)-trans-GK563
- · Article number: 25732
- **Application of the substance / the mixture** This product is for research use - Not for human or veterinary diagnostic or therapeutic use.
- · Details of the supplier of the safety data sheet
- **Manufacturer/Supplier:** Cayman Chemical Co. 1180 E. Ellsworth Rd. Ann Arbor, MI 48108 USA
- Information department: Product safety department
 Emergency telephone number: During normal opening times: +1 (734) 971-3335 US/CANADA: 800-424-9300 Outside US/CANADA: 703-741-5970

2 Hazard(s) identification



Printing date 06/07/2023

Revision date 06/07/2023

Trade name: (±)-trans-GK563

Image: State of the second state of	
gnal word Dangerizard-determining components of labeling:ethyl acetateizard statementsizard statementsiz25 Highly flammable liquid and vapor.i29 Causes serious eye irritation.i36 May cause drowsiness or dizziness.ecautionary statementsi20Keep away from heat/sparks/open flames/hot surfaces No smokiri20Ground/bond container and receiving equipment.i21i22i23i24i24i25i26i27i28i29i29i29i29i20i20i20i21i21i22i23i23i24i24i25i29i29i29i29i20i20i20i21i22i23i23i23i24i24i25i29	
gnal word Dangerizard-determining components of labeling:ethyl acetateizard statementsizard statementsiz25 Highly flammable liquid and vapor.i29 Causes serious eye irritation.i36 May cause drowsiness or dizziness.ecautionary statementsi20Keep away from heat/sparks/open flames/hot surfaces No smokiri20Ground/bond container and receiving equipment.i21i22i23i24i24i25i26i27i28i29i29i29i29i20i20i20i21i21i22i23i23i24i24i25i29i29i29i29i20i20i20i21i22i23i23i23i24i24i25i29	
gnal word Dangerizard-determining components of labeling:ethyl acetateizard statementsizard statementsiz25 Highly flammable liquid and vapor.i29 Causes serious eye irritation.i36 May cause drowsiness or dizziness.ecautionary statementsi20Keep away from heat/sparks/open flames/hot surfaces No smokiri20Ground/bond container and receiving equipment.i21i22i23i24i24i25i26i27i28i29i29i29i29i20i20i20i21i21i22i23i23i24i24i25i29i29i29i29i20i20i20i21i22i23i23i23i24i24i25i29	
gnal word Dangerizard-determining components of labeling:ethyl acetateizard statementsizard statementsiz25 Highly flammable liquid and vapor.i29 Causes serious eye irritation.i36 May cause drowsiness or dizziness.ecautionary statementsi20Keep away from heat/sparks/open flames/hot surfaces No smokiri20Ground/bond container and receiving equipment.i21i22i23i24i24i25i26i27i28i29i29i29i29i20i20i20i21i21i22i23i23i24i24i25i29i29i29i29i20i20i20i21i22i23i23i23i24i24i25i29	
ard-determining components of labeling:ethyl acetatetzard statements225 Highly flammable liquid and vapor.319 Causes serious eye irritation.336 May cause drowsiness or dizziness.ecautionary statements210Keep away from heat/sparks/open flames/hot surfaces No smokir40Ground/bond container and receiving equipment.41Use explosion-proof electrical/ventilating/lighting/equipment.4243Take precautionary measures against static discharge.461Avoid breathing dust/fume/gas/mist/vapors/spray	
ethyl acetateazard statements225 Highly flammable liquid and vapor.219 Causes serious eye irritation.36 May cause drowsiness or dizziness.ecautionary statements210Keep away from heat/sparks/open flames/hot surfaces No smokir240Ground/bond container and receiving equipment.241Use explosion-proof electrical/ventilating/lighting/equipment.242243Take precautionary measures against static discharge.261Avoid breathing dust/fume/gas/mist/vapors/spray	
azard statements225 Highly flammable liquid and vapor.219 Causes serious eye irritation.236 May cause drowsiness or dizziness.ecautionary statements210Keep away from heat/sparks/open flames/hot surfaces No smokir240Ground/bond container and receiving equipment.241Use explosion-proof electrical/ventilating/lighting/equipment.242Use only non-sparking tools.243Take precautionary measures against static discharge.261Avoid breathing dust/fume/gas/mist/vapors/spray	
225 Highly flammable liquid and vapor.319 Causes serious eye irritation.336 May cause drowsiness or dizziness.ecautionary statements210Keep away from heat/sparks/open flames/hot surfaces No smokir240Ground/bond container and receiving equipment.241Use explosion-proof electrical/ventilating/lighting/equipment.242Use only non-sparking tools.243Take precautionary measures against static discharge.261Avoid breathing dust/fume/gas/mist/vapors/spray	
319 Causes serious eye irritation.336 May cause drowsiness or dizziness.acautionary statements210Keep away from heat/sparks/open flames/hot surfaces No smokir240Ground/bond container and receiving equipment.241Use explosion-proof electrical/ventilating/lighting/equipment.242Use only non-sparking tools.243Take precautionary measures against static discharge.261Avoid breathing dust/fume/gas/mist/vapors/spray	
B36 May cause drowsiness or dizziness.ecautionary statements210Keep away from heat/sparks/open flames/hot surfaces No smokir240Ground/bond container and receiving equipment.241Use explosion-proof electrical/ventilating/lighting/equipment.242Use only non-sparking tools.243Take precautionary measures against static discharge.261Avoid breathing dust/fume/gas/mist/vapors/spray	
ecautionary statements210Keep away from heat/sparks/open flames/hot surfaces No smokir240Ground/bond container and receiving equipment.241Use explosion-proof electrical/ventilating/lighting/equipment.242Use only non-sparking tools.243Take precautionary measures against static discharge.261Avoid breathing dust/fume/gas/mist/vapors/spray	
 Keep away from heat/sparks/open flames/hot surfaces No smokin Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray 	
40Ground/bond container and receiving equipment.41Use explosion-proof electrical/ventilating/lighting/equipment.42Use only non-sparking tools.43Take precautionary measures against static discharge.61Avoid breathing dust/fume/gas/mist/vapors/spray	
41Use explosion-proof electrical/ventilating/lighting/equipment.42Use only non-sparking tools.43Take precautionary measures against static discharge.61Avoid breathing dust/fume/gas/mist/vapors/spray	ng.
Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray	
Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray	
Avoid breathing dust/fume/gas/mist/vapors/spray	
71 Use only outdoors or in a well-ventilated area.	
80 Wear protective gloves/protective clothing/eye protection/face prote	ction
03+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing water/shower.	
04+P340 IF INHALED: Remove person to fresh air and keep comfortable for	breathing.
05+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove present and easy to do. Continue rinsing.	
Call a poison center/doctor if you feel unwell.	
37+P313 If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
.03+P233 Store in a well-ventilated place. Keep container tightly closed.	
.03+P235 Store in a well-ventilated place. Keep cool.	
05 Store locked up.	
Dispose of contents/container in accordance with local/regional/nati	ional/internation
regulations.	
assification system:	
PA ratings (scale 0 - 4)	
Health = 2	
Fire = 3	
2×0 Reactivity = 0	
/IS-ratings (scale 0 - 4)	

HEALTH2Health = 2FIRE3Fire = 3REACTIVITY0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

(Contd. on page 3)

US

Printing date 06/07/2023

Revision date 06/07/2023

(Contd. from page 2)

99.0%

1.0%

Trade name: (±)-trans-GK563

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

 \cdot **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

CAS: 79-20-9 Methyl acetate RTECS: Al9100000

Other ingredients

2351820-19-2 (±)-trans-GK563

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

- · Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

• **Reference to other sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

US

Printing date 06/07/2023

Revision date 06/07/2023

Trade name: (±)-trans-GK563

See Section 13 for disposal information.	(Contd. from page 3)
• PAC-1:	
79-20-9 Methyl acetate	250 ppm
PAC-2:	
79-20-9 Methyl acetate	1,700 ppm
PAC-3:	
79-20-9 Methyl acetate	10000* ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- Storage: Store in accordance with information listed on the product insert.
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

79-20-9 Methyl acetate

- PEL Long-term value: 610 mg/m³, 200 ppm
- REL Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm
- TLV Short-term value: 250 ppm Long-term value: 200 ppm

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 5)

US

Printing date 06/07/2023

Revision date 06/07/2023

Trade name: (±)-trans-GK563

(Contd. from page 4)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information		
· Appearance:		
Form:	Liquid	
Color:	According to product specification	
· Odor:	Pleasant	
• Structural Formula	C16H22O2	
• Molecular Weight	246.3 g/mol	
· Odor threshold:	Not determined.	
• Formulation	A solution in methyl acetate	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	-98 °C (-144.4 °F)	
Boiling point/Boiling range:	57 °C (134.6 °F)	
· Flash point:	-13 °C (8.6 °F)	
· Flammability (solid, gaseous):	Highly flammable.	
· Auto igniting:	454 °C (849.2 °F)	
· Decomposition temperature:	Not determined.	
		(Contd. on page 6)

Printing date 06/07/2023

Revision date 06/07/2023

Trade name: (±)-trans-GK563

	(Contd. from page 5)
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
[·] Explosion limits: Lower: Upper:	3.1 Vol % 16 Vol %
 Vapor pressure at 20 °C (68 °F): Vapor pressure at 50 °C (122 °F): 	220 hPa (165 mm Hg) 800 hPa (600 mm Hg)
[·] Density at 20 °C (68 °F):	0.93 g/cm³ (7.76085 lbs/gal)
 Bulk density: Relative density Vapor density Evaporation rate 	1 kg/m³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water at 20 °C (68 °F): 	330 g/l
· Partition coefficient (n-octanol/wate	r): Not determined.
 Viscosity: Dynamic at 20 °C (68 °F): Kinematic: SOLUBILITY 	0.381 mPas Not determined. Chloroform: slightly soluble; DMSO: slightly soluble; Methanol: slightly soluble
 Solvent content: Organic solvents: VOC content: 	99.0 % 0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	1.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- \cdot Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: strong oxidizing agents
- · Hazardous decomposition products: carbon dioxide, carbon monoxide

(Contd. on page 7)

US

Printing date 06/07/2023

Revision date 06/07/2023

Trade name: (±)-trans-GK563

(Contd. from page 6)

11 Toxicolo	gical in	formation
· Informatio · Acute toxi		cological effects
· LD/LC50 v	alues tha	t are relevant for classification:
79-20-9 Me	ethyl acet	ate
Oral	LD50	6,482 mg/kg (rat)
Inhalative	LC50/4 h	>49.2 mg/l (rabbit)
• Additional	n: No irrita : Irritating ion: No se toxicolo ct shows ns:	ant effect. effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation methods for
		Agency for Research on Cancer)
•		nts is listed.
· NTP (Natio	onal Toxi	cology Program)
None of the	e ingredie	nts is listed.
· OSHA-Ca	(Occupat	ional Safety & Health Administration)
None of the	e ingredie	nts is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

US

Printing date 06/07/2023

Revision date 06/07/2023

(Contd. from page 7)

Trade name: (±)-trans-GK563

• Uncleaned packagings:
 • Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number DOT, IMDG, IATA	UN1231
UN proper shipping name DOT, IATA IMDG	Methyl acetate solution METHYL ACETATE solution
Transport hazard class(es)	
DOT	
TUMMARE COLO 3	
· Class · Label	3 Flammable liquids 3
IMDG, IATA	3
· Class · Label	3 Flammable liquids 3
Packing group DOT, IMDG, IATA	11
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids 33 F-E,S-D B
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
	(Contd. on page

Printing date 06/07/2023

Revision date 06/07/2023

Trade name: (±)-trans-GK563

(Contd. from page 8)

· IATA · Remarks:	When sold in quantities of less than or equal to 1 mL, or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.
· UN "Model Regulation":	UN 1231 METHYL ACETATE SOLUTION, 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

79-20-9 Methyl acetate

ACTIVE

Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes (Contd. on page 10)

Printing date 06/07/2023

Revision date 06/07/2023

Trade name: (±)-trans-GK563

(Contd. from page 9) no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.	
 Department issuing SDS: Environment protection department. Contact: - Date of preparation / last revision 06/07/2023 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent D50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit REL: Recommended Exposure Limit REL: Recommended Exposure Limit Fammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3	