

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2023

Revision date 03/29/2023

1 Identification

· Product identifier

· Trade name: 12(S)-HpETE

· Article number: 44570

· Application of the substance / the mixture

This product is for research use - Not for human or veterinary diagnostic or therapeutic use.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Cayman Chemical Co. 1180 E. Ellsworth Rd. Ann Arbor, MI 48108

USA

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (734) 971-3335

US/CANADA: 800-424-9300

Outside US/CANADA: 703-741-5970

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



Eye Irritation 2A

H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS02 GHS07

(Contd. on page 2)

Revision date 03/29/2023 Printing date 03/29/2023

Trade name: 12(S)-HpETE

Signal word Danger

(Contd. from page 1)

· Hazard statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed. P233

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools. P242

Take precautionary measures against static discharge. P243

Wash thoroughly after handling. P264

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337+P313

In case of fire: Use CO2, powder or water spray to extinguish. P370+P378

Store in a well-ventilated place. Keep cool. P403+P235

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64-17-5	ethanol	99.99%	
RTECS: KQ6300000			

Other ingredients

71774-10-2 12(S)-HpETE 0.01%

Revision date 03/29/2023 Printing date 03/29/2023

Trade name: 12(S)-HpETE

(Contd. from page 2)

4 First-aid measures

- · Description of first aid measures
- · **General information:** Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air: consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1,800 ppm
3300* ppm
15000* ppm

Printing date 03/29/2023 Revision date 03/29/2023

Trade name: 12(S)-HpETE

(Contd. from page 3)

7 Handling and storage

· Handling:

Precautions for safe handling

No special precautions are necessary if used correctly.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Avoid prolonged or repeated exposure.

Keep away from sources of ignition.

Take precautionary measures against static discharge.re.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage: Store in accordance with information listed on the product insert.
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1000 ppm

A3

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Printing date 03/29/2023 Revision date 03/29/2023

Trade name: 12(S)-HpETE

(Contd. from page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

o Da	10 00	and	chemi	0.0	DEOD	OFFICE
~	งรเษต	antu	CHEIII	U.G		

Information on basic physical and c	hemical properties
· General Information	
· Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Alcohol-like
Structural Formula	C20H32O4
Molecular Weight	336.5 g/mol
Odor threshold:	Not determined.
· Formulation	A solution in ethanol
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-114 °C (-173.2 °F)
Boiling point/Boiling range:	78 °C (172.4 °F)
· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	3.3 Vol %
Upper:	19 Vol %
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
Vapor pressure at 50 °C (122 °F):	280 hPa (210 mm Hg)
· Density at 20 °C (68 °F):	0.79 g/cm³ (6.59255 lbs/gal)
Relative density	Not determined.

(Contd. on page 6)

Printing date 03/29/2023 Revision date 03/29/2023

Trade name: 12(S)-HpETE

	(Contd. from page
· Vapor density · Evaporation rate	Not determined. Not determined.
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	1,000 g/l
· Partition coefficient (n-octanol/w	ater): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	1.2 mPas
Kinematic:	Not determined.
SOLUBILITY	0.1 M Na2CO3: 2 mg/ml; DMF: Miscible; DMSO: Miscible Ethanol: Miscible; PBS pH 7.2: 0.8 mg/ml
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	99.99 %
	999.9 g/l / 8.34 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: strong oxidizing agents
- · Hazardous decomposition products: carbon dioxide; carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
64-17-5 et	64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat)	
Inhalative	LC50/4 h	117–125 mg/l (rat)	

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 7)

Printing date 03/29/2023 Revision date 03/29/2023

Trade name: 12(S)-HpETE

(Contd. from page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

64-17-5 ethanol

1

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 T	rans	port i	nfor	mati	on

· UN-Number · DOT, IMDG, IATA	UN1170
· UN proper shipping name · DOT · IMDG	Ethanol solutions ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) Ethanol solution

(Contd. on page 8)

Printing date 03/29/2023 Revision date 03/29/2023

Trade name: 12(S)-HpETE

(Contd. from page 7) · Transport hazard class(es) · DOT · Class 3 Flammable liquids · Label · IMDG, IATA · Class 3 Flammable liquids · Label 3 · Packing group DOT, IMDG, IATA Ш · Environmental hazards: Not applicable. · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-D Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 1L Code: E2 Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IATA · Remarks: When sold in quantities of less than or equal to 1 mL, or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity. · UN "Model Regulation": UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II

Printing date 03/29/2023 Revision date 03/29/2023

Trade name: 12(S)-HpETE

(Contd. from page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

64-17-5 ethanol

ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

- · Carcinogenic categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value)

64-17-5 ethanol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

- · Department issuing SDS: Environment protection department.
- Contact: -
- Date of preparation / last revision 03/29/2023
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 10)

Printing date 03/29/2023 Revision date 03/29/2023

Trade name: 12(S)-HpETE

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

(Contd. from page 9)